

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Previously Presented) A method in a computer system for performing a transaction that includes multiple requests, the method comprising:
  - an application interface of a client computer receiving a request from an application program;
  - the application interface associating a transaction identifier with the request, wherein the transaction identifier identifies a transaction that the request is associated with;
  - the application interface forming a message including the transaction identifier and the request;
  - the application interface sending the message to a server, comprising the steps of opening a connection with the server, sending the message over the connection, initializing a timer upon receipt of a reply from the server, determining whether a timeout period has expired before another request is received from the application program, keeping the connection open so long as another request is received before the timeout period has expired, and closing the connection when the timeout period has expired before another request is received from the application program;
  - the server receiving the message; and
  - the server processing the request in a context of the transaction identified by the transaction identifier in the message.
2. (Original) The method as claimed in claim 1, further comprising:
  - the application interface associating a sequence indicator to the request, wherein the sequence indicator indicates in what sequence the server should process the request within the context of the transaction; and
  - wherein forming the message comprises including the sequence indicator in the message.
3. (Canceled)

4. (Original) The method as claimed in claim 1, further comprising:  
receiving a reply from the server in response to the request;  
determining that the reply includes a redirect request that indicates that the request should be sent to another server; and  
sending the message to the another server.

5. (Original) The method as claimed in claim 1, further comprising:  
the server allocating a database connection to the transaction; and  
the server processing the requests that form a part of the transaction over the database connection allocated to the transaction.

6. (Original) The method as claimed in claim 5, further comprising:  
the application interface including a sequence indicator in the message, wherein the sequence indicator indicates in what sequence the server should process the request within the context of the transaction; and  
wherein processing the requests comprises processing the requests in an order indicated by the sequence indicator.

7. (Previously Presented) A method in a computer system for a client to perform multiple requests in the context of a transaction, the method performed by an application interface associated with the client, the method comprising:  
receiving a request from an application program;  
associating a transaction identifier with the request, wherein the transaction identifier identifies a transaction that the request is associated with;  
forming a message including the transaction identifier and the request; and  
sending the message to a server, comprising the steps of opening a connection with the server, sending the message over the connection, initializing a timer upon receipt of a reply from the server, determining whether a timeout period has expired before another request is received from the application program, keeping the connection open so long as another request is received before the timeout period has expired, and closing the connection

when the timeout period has expired before another request is received from the application program.

8. (Original) The method as claimed in claim 7, further comprising assigning the transaction identifier to the transaction if the request is a request to open a new transaction.

9. (Original) The method as claimed in claim 7, further comprising:  
associating a sequence indicator with the request, wherein the sequence indicator indicates in what sequence the server should process the request within the context of the transaction; and

wherein forming the message comprises including the sequence indicator within the message.

10. (Original) The method as claimed in claim 7, further comprising:  
multiplexing together multiple requests that are destined for the server; and  
sending the multiple requests to the server in a multiplexed format.

11. (Original) The method as claimed in claim 7, further comprising:  
receiving a reply from the server in response to sending the message; and  
sending the reply to the application program.

12. (Previously Presented) A method in a computer system for a client to redirect a request from a first server to a second server, the method performed by an application interface, the method comprising:

receiving a request from an application program, wherein the application interface is separate from the application program;

formatting the request into a message;

sending the message to the first server;

receiving a reply from the first server in response to the message, wherein the reply includes a redirect request that indicates that the second server is a correct destination for the message; and

sending the message to the second server without involving the application program.

13. (Previously Presented) The method as claimed in claim 12, wherein sending the message to the first server comprises:

- opening a connection with the server;
- sending the message over the connection;
- initializing a timer upon receipt of a reply from the server;
- determining whether a timeout period has expired before another request is received from the application program; and
- closing the connection when the timeout period has expired.

14. (Original) The method as claimed in claim 12, further comprising the application interface storing the redirect request so that subsequent similar requests can be initially directed to the second server rather than to the first server.

15. (Previously Presented) A method in a computer system for a client to send one or more messages to a server, the method comprising:

- opening a connection with the server;
- sending the one or more message over the connection;
- initializing a timer upon receipt of a reply from the server;
- determining whether a timeout period has expired before another request is received from an application program of the client;
- keeping the connection open so long as another request is received before the timeout period has expired; and
- closing the connection when the timeout period has expired before another request is received from the application program.

16. (Previously Presented) The method as claimed in claim 15, wherein determining whether the timeout period has expired comprises comparing a value of the timer to the timeout period.

17. (Original) The method as claimed in claim 15, further comprising:  
receiving another request destined for the server within the timeout period; and  
sending the another request to the server over the connection.

18. (Original) The method as claimed in claim 17, further comprising:  
re-initializing and re-starting the timer when a reply corresponding to the another  
request is received from the server.

19. (Canceled)

20. (Canceled)

21. (Canceled)

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (Canceled)

26. (Canceled)

27. (Canceled)

28. (Previously Presented) A computer system for processing requests from  
application programs, the computer system comprising:

a processor for executing an application interface which receives requests destined for  
the server from at least one application program, associates transaction identifiers with each

of the requests that are associated with transactions, and forms messages including the transaction identifiers and the requests; and

an interface to the server, coupled to the processor through a bus, which sends the messages to the server by opening a connection with the server, sending the messages over the connection, initializing a timer upon receipt of a reply from the server, determining whether a timeout period has expired before a subsequent request is received from the application program, keeping the connection open so long as another request is received before the timeout period has expired, and closing the connection when the timeout period has expired before another request is received from the application program.

29. (Original) The computer system as claimed in claim 28, wherein the processor is further for associating sequence indicators with the requests, wherein the sequence indicators indicate the order that the requests within a transaction should be performed by the server.

30. (Original) A computer system for processing requests from application programs, the computer system comprising:

a processor for executing an application interface which receives a request destined for a first server from an application program, formats the request into a message, sends the message to the first server via a network interface, receives a reply from the first server in response to the message, wherein the reply includes a redirect request that indicates that a second server is a correct destination for the message, and sends the message to the second server via the network interface without involving the application program; and

the network interface, coupled to the processor through a bus, which sends the message to the first server and the second server.

31. (Previously Presented) A computer system for processing requests from application programs, the computer system comprising:

a processor for executing an application interface which receives requests destined for a server from at least one application program, opens a connection with the server, sends the one or more requests over the connection, initializes a timer upon receipt of a reply from the

server, determines whether a timeout period has expired before another request is received from the at least one application program, keeps the connection open so long as another request is received before the timeout period has expired, and closes the connection when the timeout period has expired before another request is received from the application program; and

an interface to the server, coupled to the processor through a bus, which sends the one or more requests to the server.

32. (Original) The computer system as claimed in claim 31, wherein the processor is further for sending one or more additional requests destined for the server over the connection during the timeout period.

33. (Canceled)

34. (Canceled)

35. (Canceled)

36. (Previously Presented) A computer-readable medium holding computer executable instructions, the computer-readable medium for performing a method in a computer system for a client to perform multiple requests in the context of a transaction, the method performed by an application interface associated with the client, the method comprising:

- receiving a request from an application program;
- associating a transaction identifier with the request, wherein the transaction identifier identifies a transaction that the request is associated with;
- forming a message including the transaction identifier and the request; and
- sending the message to a server, comprising the steps of opening a connection with the server, sending the message over the connection, initializing a timer upon receipt of a reply from the server, determining whether a timeout period has expired before another request is received from the application program, keeping the connection open so long as

another request is received before the timeout period has expired, and closing the connection when the timeout period has expired before another request is received from the application program.

37. (Original) A computer-readable medium holding computer executable instructions, the computer-readable medium for performing a method in a computer system for a client to redirect a request from a first server to a second server, the method performed by an application interface comprising:

- receiving a request from an application program, wherein the application interface is separate from the application program;
- formatting the request into a message;
- sending the message to the first server;
- receiving a reply from the first server in response to the message, wherein the reply includes a redirect request that indicates that the second server is a correct destination for the message; and
- sending the message to the second server without involving the application program.

38. (Previously Presented) A computer-readable medium holding computer executable instructions, the computer-readable medium for performing a method in a computer system for a client to send one or more messages to a server, the method comprising:

- opening a connection with the server;
- sending the one or more message over the connection;
- initializing a timer upon receipt of a reply from the server;
- determining whether a timeout period has expired before another message is received for sending to the server;
- keeping the connection open so long as another message is received before the timeout period has expired; and
- closing the connection when the timeout period has expired before another message is received.



**DOCKET NO.:** MSFT-0565/146947.1  
**Application No.:** 09/717,674  
**Office Action Dated:** September 8, 2006

**PATENT**

39. (Canceled)